


# AGRU PVDF-el ESD Sheet Plain

EXTRUDED



Raw Material: PVDF-el ESD  
Polymer

Color: Black

Density: 1.78 g/cm<sup>3</sup>

Surface Protection: Protection foil  
on both sides

Traceability: Fabricator's label  
including lot number on each  
sheet

Certificates: ISO 9001 and ISO  
14001

Dimensions (length x width):  
3000 mm x 1500 mm

Product Code	Fiber-free Thickness [mm]	
4L.600.3015.03	3	± 0.17
4L.600.3015.04	4	± 0.20
4L.600.3015.06	6	± 0.26
4L.600.3015.08	8	± 0.32

All information and statements submitted on is paper are based on our current knowledge and experience. In view of the many factors that may affect processing and application, these data do not relieve users from responsibility of carrying out their own tests and experiments; neither do they imply any legally binding assurance of certain properties or of suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any proprietary rights and existing laws, standards, and legislation are observed. The statements about all product relevant properties in our valid catalogues, documents and price lists have to be considered.



Commerical Registration No. 171838d  
Commerical Registration Court. LG Steyr  
RZ00AT2L560

Raiffeisenbank Bad Hall  
IBAN: AT78 3456 0000 0210 1061

PVDF-K - 32

