

AGRU PVDF-Flex Sheet Fabric- Backed

EXTRUDED



Raw Material: PVDF-Flex Polymer
 Fabric Backing: SK+ Synthetic Fabric
 Color: Natural / opaque
 Density: 1.77 g/cm³
 Surface Protection: Protection foil on both sides
 Traceability: Fabricator's label including lot number on each sheet
 Certificates: ISO 9001 and ISO 14001
 Dimensions (length x width): 3000 mm x 1500 mm

| Fiber-free Thickness [mm] | |
|---------------------------|--------|
| 2.3 | ± 0.23 |
| 3 | ± 0.30 |

All information and statements submitted on this paper are based on our current knowledge and experience. In view of the many factors that may affect processing and application, these data do not relieve users from responsibility of carrying out their own tests and experiments; neither do they imply any legally binding assurance of certain properties or of suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any proprietary rights and existing laws, standards, and legislation are observed. The statements about all product relevant properties in our valid catalogues, documents and price lists have to be considered.



Commercial Registration No. 171838d
 Commercial Registration Court. LG Steyr
 RZ00AT2L560

Raiffeisenbank Bad Hall
 IBAN: AT78 3456 0000 0210 1061

PVDF-FLEX-K - 4K

AGRU America, Inc.
 500 Garrison Road
 Georgetown, SC 29440 USA

(800) 373-2478 | Fax: (843) 546-0516
agru.life/semi-finished

This information is provided for reference purposes only and is not intended as a warranty or guarantee. AGRU America, Inc. assumes no liability in connection with the use of this information.



www.agruamerica.com