

# AGRU PVDF-Flex Sheet Fabric- Backed

EXTRUDED, ROLLED



**Raw Material:**  
PVDF-Flex Polymer

**Fabric Backing:**  
SK+ Synthetic Fabric

**Color:**  
Natural / opaque

**Density:**  
1.77 g/cm<sup>3</sup>

**Traceability:**  
Fabricator's label including lot number  
on each sheet

**Certificates:**  
ISO 9001 and ISO 14001

**Dimensions (length x width):**  
10000 mm x 1500 mm

Product Code	Fiber-free Thickness [mm]	
	Value	Tolerance
4K.671.1150.23	2.3	± 0.23
4K.671.1150.30	3	± 0.30

All information and statements submitted on this paper are based on our current knowledge and experience. In view of the many factors that may affect processing and application, these data do not relieve users from the responsibility of carrying out their own tests and experiments; neither do they imply any legally binding assurance of certain properties or of suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any proprietary rights and existing laws, standards and legislation are observed. The statements about all product relevant properties in our valid catalogs, documents and price lists have to be considered.



Commercial Registration No. 171838d  
Commercial Registration Court. LG Steyr  
RZ00AT2L560

Raiffeisenbank Bad Hall  
IBAN: AT78 3456 0000 0210 1061

PVDF-FLEX-K - 4K

**AGRU America, Inc.**  
500 Garrison Road  
Georgetown, SC 29440 USA

(800) 373-2478 | Fax: (843) 546-0516  
[agru.life/semi-finished](http://agru.life/semi-finished)



[www.agruamerica.com](http://www.agruamerica.com)