

AGRU PVDF Sheet Pressed

Product Code	Sheet Thickness [mm]	
	Min	Max
30.640.2010.10	10	-0 / +0.38
30.640.2010.12	12	-0 / +0.38
30.640.2010.15	15	-0 / +0.53
30.640.2010.20	20	-0 / +0.68
30.640.2010.25	25	-0 / +0.83
30.640.2010.30	30	-0 / +0.98
30.640.2010.40	40	-0 / +1.28

Raw Material:
PVDF Homopolymer

Color:
Natural / opaque

Density:
1.78 g/cm³

Traceability:
Fabricator's label including lot number on each sheet

Certificates:
ISO 9001 and ISO 14001

Dimensions (length x width):
2000 mm x 1000 mm

All information and statements submitted on this paper are based on our current knowledge and experience. In view of the many factors that may affect processing and application, these data do not relieve users from the responsibility of carrying out their own tests and experiments; neither do they imply any legally binding assurance of certain properties or of suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any proprietary rights and existing laws, standards and legislation are observed. The statements about all product relevant properties in our valid catalogs, documents and price lists have to be considered.



Commercial Registration No. 171838d
Commercial Registration Court. LG Steyr
RZ00AT2L560

Raiffeisenbank Bad Hall
IBAN: AT78 3456 0000 0210 1061

PVDF-S - 30

AGRU America, Inc.
500 Garrison Road
Georgetown, SC 29440 USA

(800) 373-2478 | Fax: (843) 546-0516
agru.life/semi-finished

